




LEFT COAST WHITE OAK

STANDARD FINISHES



UNFINISHED



POLY FINISH



OIL FINISH



CUSTOM
FINISHES
ALSO AVAILABLE

DESCRIPTION

Recovered solid White Oak flooring and paneling. Evoking a connection to the raw and dramatic slopes of the Cascades, Left Coast White Oak is full of inherent allure. You'll see a variety of grain patterns, knots and checks, and colors ranging from luminous soft wheat and pale caramel, to deep sun-kissed tan.



SPECIES

Quercus garryana

MILLWORK

Surfaced 4 sides, tongue & groove (ThinClad has micro-bevel), back-relieved & end-matched

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x (specified width) x 1'-10' solid random lengths (or longer, if available)

ENGINEERED: 5/8" thick x (specified width) x 1'-10' random lengths (or longer, if available). Wear layer 5/32" (4mm) thick over 1/2" (12mm) thick plywood substrate.

THINCLAD DIMENSIONS

3/8" thick x 5" face width x 1'-10' solid random lengths (or longer, if available)

SOURCE

Recovered and up-cycled byproduct from contemporary harvest of conifer trees in Pacific Northwest

SUSTAINABILITY

LEED V4

Building Product Disclosure & Optimization
Regional Priority
Low-Emitting Materials
Material Ingredients

DECLARE LABEL: Red List Approved for Unfinished, Oil & Poly Finish

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified



HARDNESS

Janka rating 1660. Suitable for high-traffic indoor environments.

CHARACTER PLUS GRADE

Unlimited color variation, bright sap, and a variety of character including knots of all sizes (including split or open knots), checking, oxide or other stains & discolorations, & other character showing the history & prior use of the material.

APPLICATION

Flooring, Cladding, Stair Treads & More

FLAME SPREAD

White Oak: 100 (class C). Class A flame retardant coatings are available.

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. for engineered

LEAD TIME


2-6 Weeks (or less)

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	GRADE	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	5" Fixed	3-8"	Character +	3/4" Thick	Unfinished, Oil or Poly	T+G
ThinClad Interior Cladding	5" Fixed	3, 4, 5" Mixed	Character +	3/8" Thick	Unfinished, Oil or Poly	T+G with Micro-Bevel
Engineered Flooring	5" Fixed	3-10"	Character +	5/8" Thick	Unfinished, Oil or Poly	T+G with Micro-Bevel

A variety of fixed and mixed widths are available up to 8" wide and custom profiles, finishes and applications are available. Also engineered up to 10" wide. Please inquire for more information.

Inquire to create your custom specification




TONGUE + GROOVE

Standard profile (other profiles available)




T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture this engineered product in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER

Declare.



ANTHOLOGY WOODS



1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com