





ANTHOLOGY
WOODS

SPECIFIER'S GUIDE
+ TECHNICAL DATA

LEGACY WHITE OAK



STANDARD FINISHES (Shown on Select Grade)



DESCRIPTION

Our FSC® Certified solid or engineered white oak wood flooring and cladding supports responsible forest management while offering a quality and elegant product. Character Grade shows an array of burrows, knots and checks, while Select Grade offers a more uniform and polished appearance.

SPECIES

Quercus alba

MILLWORK

Surfaced 4 sides, tongue and groove
Flooring products are back-relieved &
end matched. ThinClad planks have a
micro-bevel T&G.

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x (specified width)
x 1'-10' solid random lengths (or longer, if
available)

ENGINEERED: 5/8" thick x (specified
width) x 1'-10' random lengths (or longer,
if available). Wear layer 5/32" (4mm) thick
over a 1/2" (12mm) thick FSC certified
9-ply birch new wood substrate.

THINCLAD DIMENSIONS

3/8" thick x 5" width x 1'-10' solid random
lengths (or longer, if available)

SOURCE

Wood from sustainably-managed forests
in the eastern U.S.

SUSTAINABILITY

FSC® CERTIFIED: FSC Mixed Credit
available upon request

LEED V4

Building Product Disclosure & Optimization
Regional Priority
Low-Emitting Materials
Material Ingredients

DECLARE LABEL: Red List Approved
for Unfinished, Oil & Poly Finish

GREENGUARD GOLD: Standard Oil &
Poly Finishes are Greenguard Gold Certified



HARDNESS

Janka rating 1350. Suitable for
high-traffic indoor environments.

GRADE

SELECT: Variety in grain patterns, small
tight knots, burls, limited slightly open
checks (no shake) & unlimited natural
color variation with bright sapwood

CHARACTER: Allows unlimited color
variation, bright sapwood & a variety of
fillable defects including surface checks,
sound knots & open character

FLAME SPREAD

White Oak: 100 (class C). Class A flame
retardant coatings are available.

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. for engineered

APPLICATION

Flooring, Cladding, Stair Treads & More

LEAD TIME


2-6 Weeks (or less)

Note: Wood is a natural substance and varies in appearance.
Please refer to product images or request samples for a broader
representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	GRADE	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	5" Fixed	3-10"	Select or Character	3/4" Thick	Unfinished, Oil or Poly	T+G
ThinClad Interior Cladding	5" Fixed	3, 4, 5" Mixed	Select or Character	3/8" Thick	Unfinished, Oil or Poly	T+G
Engineered Flooring	5" Fixed	3-10"	Select or Character	5/8" or 9/16" Thick	Unfinished, Oil or Poly	T+G Micro-Bevel

A variety of fixed and mixed widths are available up to 10" wide and custom profiles, finishes and applications are available. Also engineered up to 10" wide. Please inquire for more information.

Contact us to create your custom specification




TONGUE + GROOVE

Standard profile (other profiles available)



T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL

Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

PATTERNS

We can manufacture this engineered product in a variety of patterns, including chevron and herringbone patterns.



LIVING FUTURE
CORPORATE MEMBER



Declare.

ANTHOLOGY WOODS

1.800.293.8178
www.anthologywoods.com
info@anthologywoods.com