



STANDARD FINISHES







DESCRIPTION

Take in the natural beauty of Pacific Madrone, sourced from Oregon forests. Dial in the level of knotty character or silky refinement that suits your look. Colors range through pale cream, strawberry blonde, and rich dusty rose with character accents of deep maroon.

SPECIES

Arbutus menziesii

MILLWORK

Surfaced 4 sides, tongue and groove. 3/4" thick planks are back-relieved & end matched. ThinClad planks have a micro-bevel T&G.

FLOORING + CLADDING DIMENSIONS

SOLID: 3/4" thick x 5" width x 1'-10' solid random lengths (or longer, if available) ENGINEERED: 5/8" thick x (specified width) x 1'-10' random lengths (or longer, if available). Wear layer 5/32" (4mm) thick over a 1/2" (12mm) thick plywood substrate.

THINCLAD DIMENSIONS

3/8" thick x 5" face width x 1'-10' solid random lengths (or longer, if available)

SOURCE

Recovered and upcycled byproduct from contemporary harvest of conifer trees in Pacific Northwest

SUSTAINABILITY

LEED V4

Building Product Disclosure & Optimization Regional Priority

Low-Emitting Materials Material Ingredients

DECLARE LABEL: Red List Approved for Unfinished, Oil & Poly Finish

GREENGUARD GOLD: Standard Oil & Poly Finishes are Greenguard Gold Certified







HARDNESS

Janka rating 1460. Suitable for high-traffic indoor environments.

CHARACTER PLUS GRADE

Allows unlimited color variation, bright sapwood & a variety of fillable defects including surface checks, sound knots & open characters

FLAME SPREAD

Not tested. Class A flame retardant coatings are available.

APPLICATION

Flooring, Interior Cladding, Stair Treads, Tables, Benches & Custom Applications

MINIMUM ORDER

250 sq.ft. or 500 sq.ft. for engineered.

LEAD TIME


2-6 weeks (or less)

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.


APPLICATION	STANDARD WIDTH(S)	OTHER WIDTH(S)	THICKNESS	FINISH	GRADE	PROFILE
Flooring + Interior Cladding	5" Fixed	3-8"	3/4" Thick	Unfinished, Oil or Poly	Character +	T+G
ThinClad Interior Cladding	5" Fixed	3, 4, & 5" Mixed	3/8" Thick	Unfinished, Oil or Poly	Character +	T+G Micro-Bevel
Engineered Flooring	5" Fixed	3-8"	5/8"Thick	Unfinished, Oil or Poly	Character +	T+G Micro-Bevel

Fixed and mixed widths are available (up to 8" wide by availability) and custom profiles, finishes & applications are available. Product may be engineered up to 6" wide. Please inquire for more information

Inquire to create your custom specification




TONGUE + GROOVE
Standard profile (other profiles available)




T+G: MICRO BEVEL

Standard on most engineered products, recommended for most pre-finished items & wall cladding



T+G: THINCLAD MICRO-BEVEL
Recommended for interior wall cladding



T+G: ENGINEERED WITH MICRO-BEVEL

Recommended for flooring installed over concrete sub-floor



FINISHES

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

CUSTOMIZATION

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look.

Please inquire.

PATTERNS

We can manufacture engineered products in a variety of patterns, including chevron and herringbone patterns.











ANTHOLOGY WOODS

















1.800.293.8178 www. anthologywoods.com info@anthologywoods.com