




# SUGAR TEAK



## STANDARD FINISHES



SUGAR TEAK

## DESCRIPTION

The refined elegance of reclaimed Teak meets a casual beach inspired look with our matte white "Sugar" finish available with or without a wire brushed texture. Wire brushing emphasizes a higher contrast and more aged look, whereas an even surface will produce a softly muted & more demure appearance. Color tones are in soft tan, carmel and mocha with captivating natural grain of old growth teak.

## SPECIES

Tectona grandis

## MILLWORK

Surfaced 4 sides with tongue & groove profile. Flooring products are back-relieved & end matched. ThinClad planks have a micro-bevel T&G.

## FLOORING + CLADDING DIMENSIONS

**SOLID:** 5/8" thick x 4-1/4" face width x 1'-10' solid and random lengths (or longer, if available)

**ENGINEERED:** 5/8" thick x 4-1/4" face width x 1'-10' solid and random lengths (or longer, if available). Wear layer 4mm thick over a 10mm thick plywood substrate.

## THINCLAD DIMENSIONS

3/8" thick x 4-1/2" face width x 1'-10' solid and random lengths (or longer, if available)

## LEAD TIME

2-6 weeks (or less) if in stock, 3-4 months (or less) if not in stock.

## SOURCE

Post-consumer reclaimed from sources including pole-houses, warehouses and industrial buildings in Asia

## SUSTAINABILITY

FSC® CERTIFIED: Recycled

## LEED V4

Building Product Disclosure & Optimization  
Building Life-Cycle Impact Reduction  
Low-Emitting Materials  
Material Ingredients



## HARDNESS

Teak Janka rating 1075. Heavy traffic is likely to impact the flooring surface & contribute to the beauty, patina & character over time.

## GRADE

Infrequent to frequent filled small fastener holes, insect holes, tight knots, or filled split knots. Occasional staining or discoloration & other signs of previous use. Holes & voids are pre-filled with teak and/or teak sanding dust mixed with glue.

## FLAME SPREAD

USDA FSI Teak: 76 (Class C). Class A flame retardant coatings are available.

## APPLICATION


Flooring, Interior Cladding, Stair Treads, Tables, Benches, Siding & Custom Applications. Inquire for details.

## MINIMUM ORDER

250 sq.ft. for solid. 500 sq.ft. for engineered.

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.

APPLICATION	STANDARD WIDTH(S)	THICKNESS	FINISH	PROFILE
Flooring + Interior Cladding	4-1/4" & 5" Face Widths	5/8" Thick	White Oil Sugar Finish	T+G
Engineered Flooring	4-1/4" & 5" Face Widths	5/8" Thick	White Oil Sugar Finish	T+G Micro-Bevel
ThinClad Paneling	4-1/4" & 5" Face Widths	3/8" Thick	White Oil Sugar Finish	T+G Micro-Bevel
Widths up to 7" wide and custom profiles are available (2,000 square feet minimum order). Please inquire.			Inquire to create your custom specification	



**TONGUE + GROOVE**

Standard profile (other profiles available)




**T+G: MICRO BEVEL**

Standard on most engineered products, recommended for most pre-finished items & wall cladding



**T+G: ENGINEERED WITH MICRO-BEVEL**

Recommended for flooring installed over concrete sub-floor



**T+G: THINCLAD MICRO-BEVEL**

Recommended for interior wall cladding



**FINISHES**

We apply low-VOC and eco-friendly finishes to enhance the natural beauty of the wood for durability and easy maintenance.

**CUSTOMIZATION**

We offer custom specifications for this product, including dimensions, finishes and profiles for a unique look. Please inquire.

**PATTERNS**

We can manufacture the engineered product in a variety of patterns, including chevron and herringbone patterns.



**ANTHOLOGY WOODS**

1.800.293.8178  
 www.anthologywoods.com  
 info@anthologywoods.com